

U
5550
THS

**RELATIONSHIP BETWEEN GEOLOGICAL STRUCTURE AND
GEOPHYSICAL CHARACTERISTICS OF HARD ROCKS WITH
GROUND WATER POTENTIAL:
A CASE STUDY FROM NOCHCHIYAGAMA,
ANURADHAPURA DISTRICT**

A PROJECT REPORT PRESENTED BY

CHAMINDA NUWAN THILAKARATHNE
✓

to the Board of Study in Earth Sciences of the
POSTGRADUATE INSTITUTE OF SCIENCE

*in partial fulfillment of the requirement
for the award of the degree of*

**MASTER OF SCIENCE IN ENGINEERING GEOLOGY AND
HYDROGEOLOGY**

of the

UNIVERSITY OF PERADENIYA

SRI LANKA

2004

580471

**RELATION SHIP BETWEEN GEOLOGICAL STRUCTURE AND
GEOPHYSICAL CHARACTERISTICS OF HARD ROCKS WITH
GROUNDWATER POTENTIAL**

**A CASE STUDY FROM NOCHCHIYAGAMA,
ANURADHAPURA DISTRICT**

C. N. Thilakarathne

Post Graduate Institute of Science

University of Peradeniya

Peradeniya

Sri Lanka

Deep water supply bore holes are commonly used in small scale rural and small town pipe water supply schemes in Sri Lanka. Geoelectrical resistivity investigation method is used to locate sites for these deep boreholes and to understand aquifer properties of the geological formations. However, the properly documented scientific data on these investigations are not available with many organizations who are dealing with groundwater explorations.

Present study focuses on the validity and accuracy of the resistivity method in identifying hydrogeologically important zones in the hard rock.

Under the present study geoelectrical resistivity sounding and profiling were carried out in a hard rock area covering 16 Grama Niladari divisions in the Nochiyagama Pradesiysaba area, in the Anuradhapura district. Borehole log data from 25 boreholes were used in this study for comparison with geophysical investigation results.

The geoelectrical profiling was carried out to understand the lateral variations of the geological properties at selected sites. The results of the resistivity sounding were correlated with actual borehole data and it is observed in majority of boreholes that these two types of information have a good correlation. The flushing yield of the bore holes was used to evaluate the validity of the assessment of hydrogeological conditions of well sites (good, fair or unfavorable) by resistivity investigation method and found that the results are in good agreement.